

November 2015

RUST-OFF TECHNICAL APPLICATION GUIDE

DESCRIPTION

HIGHLY EFFECTIVE RUST REMOVER FOR OUTDOOR STONE

*Unique safe pH neutral formula
Suitable for use internally and externally
Easy, ready to use formula
Fast acting results*

Universeal Rust-Off is a ready-to-use, non-acid rust remover suitable for use on many types of natural stone surfaces without causing damage. Can be used internally or externally.

Universeal Rust-Off is effective for dissolving problematic rust stains. Causes for these stains may be iron containing fertilizers, metal garden furniture, leaking heating systems, etc.

DIRECTIONS FOR USE

- 1) Generously apply undiluted product to the dry surface and distribute with a brush. A purple discolouration shows the start of the reaction.
- 2) Allow to work for about 5 minutes, 10 minutes maximum. Do not allow product to dry.
- 3) After working time, rinse off with plenty of water.

Important: working time must not exceed 10 minutes. Repeat procedure in case of unsatisfactory results. Some stone and coloured concrete may change colour after treatment with Universeal Rust-Off.

Please Note: Always try product in an inconspicuous area prior to use.

COVERAGE

Up to 10m² per litre.

Coverage varies depending on surface contamination.

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

H315: Causes skin irritation
H317: May cause allergic skin reaction.
H319: Causes serious eye irritation.
H335: May cause respiratory irritation.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Product SDS sheet available to download from the Universeal website.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.



Usage Guidelines

Dwell Time	Applications/Coats	Application Method	Dilution
5-10 mins	1-3 applications	Brush/Roller	Undiluted

